


EDxtreme Dynamometer Specifications

DILLON

Model	Capacity x Resolution (normal/enhanced)			Body Construction and Overload Design
EDx-1T (EDx-2.5K)	2,500 lbf x 2/0.5	1,000 kgf x 1/0.2	10,000 N x 10/2	Aircraft quality 2024 Aluminum 700% Ultimate overload protection
EDx-2T (EDx-5K)	5,000 lbf x 5/1	2,000 kgf x 2/0.5	20,000 N x 20/5	
EDx-5T (EDx-10K)	10,000 lbf x 10/2	5,000 kgf x 5/1	50,000 N x 50/10	
EDx-10T (EDx-25K)	25,000 lbf x 20/5	10,000 kgf x 10/2	100,000 N x 100/20	Aircraft quality E4340 Alloy Steel 500% Ultimate overload protection
EDx-20T (EDx-50K)	50,000 lbf x 50/10	20,000 kgf x 20/5	200,000 N x 200/50	
EDx-50T (EDx-100K)	100,000 lbf x 100/20	50,000 kgf x 50/10	500,000 N x 500/100	
EDx-75T (EDx-160K)	160,000 lbf x 100/50	75,000 kgf x 50/20	-----	Aircraft quality E4340 Alloy Steel 400% Ultimate overload protection
EDx-100T (EDx-220K)	220,000 lbf x 200/50	100,000 kgf x 100/20	-----	
EDx-150T (EDx-330K)	330,000 lbf x 200/100	150,000 kgf x 100/50	-----	
EDx-250T (EDx-550K)	550,000 lbf x 500/200	250,000 kgf x 200/50	-----	

Note: Model in parenthesis shows U.S. convention for describing capacities.

Dimensions Dimensions shown are nominal and subject to tolerances										
Model		A	B	C	D	E	F	G	H	J
EDx-1T	inch	10.6	5.0	7.8	1.06	0.75	15.3	13.4	1.36	1.69
	mm	269	127	198	26	19	389	340	34	43
EDx-2T	inch	10.6	5.0	7.8	1.06	0.75	15.3	13.4	1.36	1.69
	mm	269	127	198	26	19	389	340	34	43
EDx-5T	inch	11.4	5.3	8.1	1.38	1.00	17.8	15.8	2.17	2.28
	mm	289	135	206	35	25	451	402	56	58
EDx-10T	inch	11.5	5.3	7.9	1.97	1.38	21.6	18.8	3.67	3.25
	mm	291	133	201	50	35	548	478	93	83
EDx-20T	inch	13.7	6.0	9.0	2.75	2.0	29.7	25.2	5.7	5.0
	mm	348	152	229	70	51	754	640	146	127
EDx-50T	inch	15.8	6.8	10.3	3.88	2.75	40.5	34.3	9.3	7.3
	mm	400	172	262	99	70	1029	870	235	184
EDx-75T	inch	16.5	7.8	10.3	3.88	2.75	40.5	34.3	8.9	7.3
	mm	419	197	262	99	70	1030	870	225	184
EDx-100T	inch	18.0	7.8	11.0	5.00	3.25	47.7	40.5	11.2	7.8
	mm	457	197	280	127	83	1211	1027	284	200
EDx-150T	inch	21.0	8.8	12.6	5.25	3.75	53.9	45.6	12.3	9.0
	mm	533	222	321	133	95	1368	1159	313	229
EDx-250T	inch	27.0	9.8	17.5	8.5	5.00	75.8	62.8	17.9	13.0
	mm	686	248	445	216	127	1925	1595	454	330



EDxtreme Electronic Dynamometer

Dynamometer Specifications

- Enclosure:** Designed to NEMA4X/IP55.
Suitable for continuous outdoor use.
- Accuracy:** 0.1% of capacity up to EDx-50T.*
0.3% of capacity for EDx-75T and above.*
- Repeatability:** 0.1% of capacity up to EDx-50T.*
0.3% of capacity for EDx-75T and above.*
* Normal resolution mode with Dillon provided shackles.
- Proof Load:** 150% of capacity up to EDx-75T.
110% of capacity Edx-100T and above.
- Ultimate Overload:** See table on reverse.
- Safe Overload:** 200% of capacity
- Body Protection:** Aluminum and alloy steel capacities are powder coated.
- Bearings:** Unmatched repeatability attained by needle bearings in shackle pin holes up to EDx-5T. Shackle pin acts as inner race.
- Shackles:** Forged industry standard anchor shackles. Models up to EDx-5T use precision machined shackle pin.
Higher capacities use bar stock pin.
- Display:** 128 x 64 dot-graphic LCD display shows up to 6 digits 1.0" (26 mm) high plus annunciators and softkeys. Digits are .11 inches (3 mm) thick for unmatched readability.
- Display Update Rate:** 2 times per second.
- Connector:** Recessed sealed connector may be used for serial communications or connection to a Communicator remote.
- RS-232 / RS-485 Communication:** Print or extract data easily.
Continuous output can drive a scoreboard. Configurable poll character.
- Calibration:** Traceable to the National Institute of Standards and Technology. Certificate included with curve of readings. Passes only with three consecutive confirming runs, with all points in specification.
- Battery Life:** 320 hours typical use with two C-cell alkaline batteries.
40 hours typical with Radio Link system.
- Operating Temperature:** -4° F to 140° F (-20° to 60° C)
- Included with Instrument:** All include certificate of calibration, manual and batteries. Plastic carry case included for EDx-1T to EDx-50T.
Higher capacities include rugged plywood storage crate. Instruments with shackles include centering spacers (EDx-20T & up) and shackle storage crate (EDx-20T to EDx-75T). Display backlight.
- Options:** Shackles. Radio communications.

Communicator Specifications

- Enclosure:** Designed to NEMA 3 / IP44 with optional sleeve.
Suitable for protected outdoor use.
- Instrument Size:** 9.0 x 4.6 x 1.8 inch (228 x 117 x 45mm).
- Accuracy:** Not applicable. Only sends and receives digital information.
- Display:** 128 x 64 dot-graphic LCD display can show full readings up to 5 instruments.
- Battery Life:** 40 hours radio or 45 wireline using four AA alkaline batteries under typical use.
- Operating Temperature:** -4° F to 140° F (-20° to 60° C)
- Connectors:** Sealed connectors may be used for serial communications and wired connection to an EDxtreme dynamometer.
- RS-232 Communication:** Print or extract data easily. Continuous output can drive a scoreboard. Configurable poll character.
- Included with Remote:** Carry case and batteries.
- Accessories:** Rubberized case protector sleeve.
Remote wall mount bracket. Serial and remote cable assemblies.

Radio Specifications

- FCC Certified:** For unlicensed low power devices. No radio licensing or permits required for normal operation.* (In the US and Canada. Check local ordinances in other countries.)
- Frequency:** 2.4 GHz spread-spectrum operates between 2.402 – 2.478 GHz. Continuously and automatically changes frequencies many times per second for consistent, reliable communications.
- Output Level:** 10 mW (10 dBm)
- Display Update Rate:** 2 times per second with single dynamometer.
Multi-instrument networks result in reduced updates.
- Number of Networks:** 63 remotes can operate independently in the same airspace with unique channels.
- Number of Links Remote Can Control:** Up to 15 addresses are available per network channel.
- Configuration:** Address and network channels are front-panel configurable.
- Antenna:** Integral antenna.
- Range:** Open-air – Up to 300 feet, line-of-sight.
Indoors – Dependent upon environment with 150 feet common.
- Approval:** FCC ID: KQL-PKLR2400
CAN ID: CAN2268391158A
CE: EMC 89/336 Machinery Safety 98/37
- Low power radio systems are dependent upon interference levels from other radio systems and environmental conditions. Radio devices are not suitable for all applications.

Weights				
	Model	Unit Weight	Weight with Shackles	Approx. Shipping Weight
EDx-1T	lb	4.3	8.6	13
	kg	2.0	3.9	6
EDx-2T	lb	4.4	8.7	13
	kg	2.0	3.9	6
EDx-5T	lb	5.6	14	22
	kg	2.5	6.1	10
EDx-10T	lb	16	40	46
	kg	7.3	18	21
EDx-20T	lb	25	96	125
	kg	11	43	56
EDx-50T	lb	38	238	296
	kg	17	108	134
EDx-75T	lb	54	250	325
	kg	25	114	145
EDx-100T	lb	70	410	480
	kg	32	186	218
EDx-150T	lb	120	650	750
	kg	54	295	340
EDx-250T	lb	250	1,490	1,600
	kg	113	675	725
Communicator	lb	1	n/a	10
	kg	.5		5

AUTHORIZED DISTRIBUTORS

Ask the experts. Dillon distributors offer complete service capabilities from application assistance to sales and product support. Their experienced representatives are the most knowledgeable experts that you will find in the force measurement industry. We recommend that you consult these capable specialists for all of your measuring needs.

DILLON USA

1000 Armstrong Drive
Fairmont, MN 56031

Toll-Free: 800-368-2031
Phone: 507-238-4461
Fax: 507-238-8258
www.dillon-force.com



© Avery Weigh-Tronix 2012. All rights reserved. This publication is issued to provide outline information only which, unless agreed by Avery Weigh-Tronix in writing, may not be regarded as a representation relating to the products or services concerned. Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

DILLON UK

Foundry Lane, Smethwick
West Midlands B66 2LP

Phone: +44 (0) 845 246 6717
Fax: +44 (0) 845 246 6718
Email: sales@dillon-force.co.uk
www.dillon-force.co.uk

DILLON

**Overload Protection and
Overhead Weighing Equipment**

A division of Avery Weigh-Tronix, LLC