

DILLON *EDxtreme frequently asked questions*

Why does Dillon have two electronic dynamometers?

We observe that there are at least two types of customers with distinct needs.

1.EDjunior

Many customers are looking to do relatively simple measuring. They just want to see the display... and perhaps retain the peak load. Of course they do not want to pay extra for features that they do not use, so they will purchase whatever technology is cost effective.

2.EDxtreme

Many customers are looking for sophistication. The EDxtreme does everything, and does it well. Works stand-alone. Works with a remote – by wire or by radio. Sends information to a computer, printer or scoreboard. Ultra-accurate. Compensates for local gravity or multi-part lines. And much more!

How has the new family improved over the ED-2000 and other competitive models?

We can not possibly mention all of the improvements, but here is a list of some of the more dramatic ones:

- ✓ New price points! Our pricing makes it easier for users to justify equipment that meets their needs.
- ✓ Awesome display! This dot-graphic display has the best viewability of any LCD technology we have seen! It can be seen from angles well, has thick easy-to-read digits and produces multi-line text to make configurations a breeze.
- ✓ Improved protection! The display rests behind 1/8" thick custom-molded Lexan panels with reinforcing ribs to distribute impacts away from the display & electronics. The serial connector on the dynamometer is recessed and angled so it is less vulnerable.
- ✓ More reliable radio system! The automatic frequency hopping 2.4 GHz radio system significantly reduces interference problems that are on the rise with single frequency 916 MHz systems.
- ✓ Optimum mechanical performance! Extreme loadcell design returns the best loadcell performance available in an electronic dynamometer.
- ✓ Sophistication! The Motorola processor handles all of the functions with ease. Extract data. Establish complex networks with easy front-panel configuration.
- ✓ We have the TOTAL! Several dynamometers can network with one Communicator! Simultaneously view all individual weights as well as the total! This is a feature that you have been asking for – Now you have it!
- ✓ Simpler recalibration! Entry through the front panel eliminates need for a computer and DOS programs.

What ED-2000 characteristics are carried into the new design?

The following were cornerstone to the success of our ED-2000 and are built into the new electronic dynamometer family:

- ✓ Full range of capacities
- ✓ Easy-to-see full 6-digit display
- ✓ Industry leading resolution at 1:5000
- ✓ Safety and convenience with a remote display (wireline & radio)
- ✓ Uses common batteries
- ✓ The best warranty anywhere!

Why is the EDjunior so inexpensive?

Many companies have a \$1000 threshold for capital expenditures or additional internal approvals and red-tape. Getting the price below this threshold makes selling easier to these customers. This decrease in price point is also expected to increase your customer base.

Although the EDjunior is inexpensive, it beats the competitors on most features – a comparative matrix follows. The EDjunior is without question the best value for simple instrumentation!

What are the differences between the EDxtreme and the EDjunior?

| | EDXtreme | EDjunior |
|-------------------------------|--------------------------------|-----------------------------|
| List price | starting at \$1240 | under \$1000 |
| Accuracy | 0.1% | 0.2% |
| Capacities | up to 100,000 lbf (50,000 kgf) | up to 10,000 lbf (5000 kgf) |
| Resolution | 1:1000 or 5000 | 1:1000 |
| RS-232 | Yes | No |
| Remote display | Radio or wired | None |
| Protection | Anodize or Nickel-plate | Powder-coat paint |
| Custom units & units lock out | Yes | No |
| Carry case | Included | Accessory |

Which new dynamometer will sell better?

The EDjunior should outsell the EDxtreme according to prior sales breakdown and given the attractiveness of the new value-priced dynamometer. However, we have not had such a feature filled product as we now have in the EDxtreme..... *“We will leave this one up to you!”*

Is the EDjunior physically smaller than the EDxtreme?

The “junior” refers to features, not size. Only the 2500-lbf (1000-kgf) EDjunior capacity is smaller. The other capacities are identical in length and headroom.

How does the EDjunior compare against its competitors?

Many customers simply want to view the live reading and perhaps retain the maximum reading. The Dillon EDjunior, MSI MSI-7200 and Intercomp TL-7200 are all suitable for this.

| | Dillon EDjunior | MSI MSI-7200 | Intercomp TL6000 |
|--------------------|--|--|---|
| Cost | \$975 to \$995 | \$1150 to \$1495 | \$1150 to \$1495 |
| Accuracy | 0.2% Full scale | 0.1% Full scale | 0.1% Full scale |
| Display | Five 1.0” digits displays entire reading in full. Menus have easy-to-read text. | Four 1.0” digit display uses “x10” annunciator for numbers over 9990. Menus are not intuitive. | Five 1.2” digit display Menus are not intuitive. |
| Display resolution | 1 part in 1000 | 1 part in 1000 | 1 part in 1000 |
| NEMA design | NEMA4X | NEMA4 | NEMA4X |
| User’s manual | Printed manual (PDF on web) | on CDROM | Printed manual |
| Carry cases | \$65 to \$120 | \$250 | Price not listed |
| Finish | Powder-coat paint | Paint | Not published |
| Factor of safety | 7:1 | 5:1 | 5:1 |
| Battery life | 320 hours | 500 hours | 500 hours |
| Peak hold | Yes | Yes | Yes |
| Units of measure | lbf, kgf, N | lbf, kgf, tons, tonne, dN | lbf, kgf, tons, tonne, dN |
| Temperature range | -20° to 60° C | -20° to 60° C | -20° to 60° C |
| Warranty | 2 years | 1 year | Not published |

The EDjunior is equal or better in nearly every feature. This alone could make the EDjunior a better dynamometer. But at 20%-50% lower price and double the warranty, it is definitely the best value!

How does the EDxtreme compare against the competition?

| | Dillon EDXtreme | MSI MSI-7200 | Intercomp TL-6000 |
|--|--|---|--|
| Industry ranking | #1 | #2 | #3 (distant) |
| Cost | \$1240-\$3250 | \$1150-\$3250 | \$1150-\$3150 |
| Accuracy | 0.1% Full scale | 0.1% Full scale | 0.1% Full scale |
| Display type | Dot-graphic LCD display for superior text and off-angle viewability | 7-segment LCD with several custom annunciators | 7-segment LCD with several custom annunciators |
| Characters | Six easy-to read 1.0" digits displays entire reading in full. Menus have easy-to-read text. | Four 1.0" digit display uses "x10" annunciator for numbers over 9990. | Five 1.2" digit display uses "x1000" annunciator where needed. |
| Backlight | Available | No | No |
| Display resolution | 1 part in 5000 enhanced | 1 part in 1000 | 1 part in 1000 |
| Remote can be added easily later | Yes – plug and play | No – at time of order only | No – at time of order only |
| Computer connection to the dynamometer | Yes | No | Yes |
| NEMA design | NEMA4X | NEMA4 | NEMA4X |
| Carry cases | Included | \$250 - \$325 | Price not listed |
| User's manual | Printed with .PDF on web | on CDROM (pdf) | Printed manual |
| Finish | Anodize or Electroless-nickel | Paint | Anodize or Brushed stainless |
| Minimum factor of safety | 7:1 (aluminum) 5:1 (steel) | 5:1 (all) | 5:1 (all) |
| Communicates with computer | Yes | No | Yes |
| Battery life | 320 hours | 500 hours | 500 hours |
| Peak hold | Yes | Yes | Yes |
| Custom units of measure | Yes - two | No | No |
| Configurable units lock out | Yes | No | No |
| Temperature range | -20° to 60° C | -20° to 60° C | -20° to 60° C |
| Warranty | 2 years | 1 year | Not published |
| Radio | | | |
| Radio upgrade (pair) | \$1000 | \$1080 | \$1300 |
| Type of technology | 2.4 GHz digital spread-spectrum automatically changes frequency | 916 MHz single frequency using - on-off keying (OOK). | Not published – presumably the same as the MSI-7200 |
| Assigning addresses | Through the front panel | Change DIP switch settings on electronics. | Not published |
| Remote can control | Up to 15 links per remote | Only one link per remote | Not published |
| Number of remotes in same airspace | Up to 63 | Up to 4 | Not published |
| Send data from remote to computer | Yes - standard | Yes – add \$195 | Not published |
| Battery life | 40 hours | 100 hours | Not published |
| Range (dependent on environment) | Up to 300 feet* | Up to 200 feet* | Up to 300 feet* |
| Sum several dynamometers | Yes – all networking is standard | No | No |

How is the new radio system better?

This new radio technology is also used for wireless computer networks! These are becoming extremely popular because of their communications reliability and ability to have multiple networks active in the same airspace.

This radio system is called 2.4 GHz spread-spectrum technology and it operates by automatically changing frequency many times per second. By covering a large range of frequencies, it typically finds several bands of good communication. Thus overall communications reliability is improved.

The older 916 MHz solution is locked at one frequency. If there is interference in that range, the radio system does not function until the interference subsides.

Is the EDxtreme and Communicator backward compatible with the ED-2000 and HR-2000?

No. In order to make the EDxtreme the pinnacle of technology, we had to adopt changes that surpassed the abilities of the ED-2000. The radio technology and communication protocols are completely new. So a new Communicator does not work with an old ED-2000 and an old HR-2000 can not display readings from a new EDxtreme.

Why is the user-configurable units of measure feature so great?

Imagine:

- ✓ Compensate for local gravitational differences in weighing applications! or
- ✓ Automatically multiply by number of parts of line on a crane! or
- ✓ Use units that are not built-in, such as kip, ton, tonne or dyne! or
- ✓ Convert the force reading to stress, pressure, etc. (e.g. psi, lpi, or Pa)

The display shows the exact unit of measure and so do printouts!

The EDxtreme also has the ability to lock out various units of measure. A lifesaver for anyone that must not accidentally change to another unit of measure!

Why do the low capacity EDxtremes require bearings?

Recently we have found it much tougher to achieve accuracy specifications with Crosby forged shackle pins. The shape and rough texture of the low capacity shackle pins hinder the achievement of our high accuracy standards. As a result, we use machined shackle pins and bearings for the best mechanical performance you will find in any dynamometer.

Are there crane scale versions of these products?

Yes. They will be complete in the upcoming months and will be sent in a separate mailing.

What service aids exist for this product?

The EDxtreme, Communicator and EDjunior all have test menus that make diagnostics easier, whether on the phone or on the bench. For example, the EDxtreme conducts internal diagnostics on:

- ✓ A/D section
- ✓ Display
- ✓ Keypad
- ✓ Radio
- ✓ Battery
- ✓ Serial port

The EDxtreme and EDjunior also retain information about the calibration.

Our comprehensive service manual will be fully completed for you soon. It will include parts diagrams, procedures and troubleshooting. We will send notice the moment that we have it up on our website. In the meantime, our service technicians can answer any immediate questions that you may have.

Can the instrument firmware be customized?

Yes. We designed the EDxtreme, Communicator and EDjunior to be extremely configurable right out of the box. However there may be customers that need something unique from their systems. In higher volumes custom software may be a feasible solution to meet their individual needs.

Do you have anything to help my local marketing and sales efforts?

To assist your sales efforts, we have a great demo kit offer, plus presentations, brochures, specification sheets and more. Talk to your Dillon sales manager to find out what we can do for you!

Have more questions? Want to learn more?

We have a FAQ sheet with even more answers on our website in the distributor area. Or give us a call to see how we can help you!

DILLON
Overload Protection and
Overhead Weighing Equipment

A division of Weigh-Tronix, Inc.
Fairmont, MN U.S.A.

Toll-Free: 800-368-2031
Phone: 507-238-8796
Fax: 507-238-8258

www.dillon-force.com

