

Dillon Model CGS Cranegard

Wire Rope Hoist & Crane Overload Protection Device

Basic Cranegard Unit (without switches) includes Certificate of calibration (when applicable) and user manual.

Note: Each unit can accommodate up to four (4) option B weatherproof, or up to two (2) option C explosion proof microswitches

Model	Capacity	Minimum Set Point	Repeatability	Rope Diameter** Min	Rope Diameter Max	List Price GBP
CGS-1	2500lb (1250Kg)	100lb (50Kg)	75lb (37.5Kg)	3/16" (4.8mm)	1/2" (12.7mm)	£1640
CGS-2	5000lb (2500Kg)	200lb (100Kg)	150lb (75Kg)	3/8" (9.5mm)	7/8" (22.2mm)	£1770
CGS-3	10000lb (5000Kg)	400lb (200Kg)	300lb (150Kg)	7/16" (11.11mm)	7/8" (22.22mm)	£1780
CGS-4	20000lb (10000Kg)	800lb (400Kg)	600lb (300Kg)	5/8" (15.88mm)	1-1/4" (69.85mm)	£2840

* Multiply by three (3) for option C microswitch.

** Specify rope diameter on order.

Switch Options- Select quantity, add to base price. Specify set point(s) if factory setting is desired.

Model	Option	Switches		List Price GBP
CGS-B1	Option B	1 switch	CGS 1-3	£640
CGS-B2	Option B	2 switches	CGS 1-3	£970
CGS-B3	Option B	3 switches	CGS 1-3	£1745
CGS-B4	Option B	4 switches	CGS 1-3	£2065
CGS-4-B1	Option B	1 switch	CGS 4	£1475
CGS-4-B2	Option B	2 switches	CGS 4	£1785
CGS-4-B3	Option B	3 switches	CGS 4	£2970
CGS-4-B4	Option B	4 switches	CGS 4	£2965
CGS-C1	Option C	1 switch	CGS 1-3	£1860
CGS-C2	Option C	2 switches	CGS 1-3	£3435
CGS-4-C1	Option C	1 switch	CGS 4	£1710
CGS-4-C2	Option C	2 switches	CGS 4	£2965

Note:

1. Overload rating of all units is 2X.
2. Cables should be IRWC (Independent Wire Rope Core) with as many strands as possible.
3. Wire rope selection for any application for proper safety factor is a customer responsibility.
4. Inquire for special rope diameters not listed above.
5. Calibration performed with rope diameter specified on order.
6. The specified calibration load must not be greater than the capacity of the Cranegard or the working strength of the cable/rope specified with appropriate rating reductions for clamping.
7. Factory calibration of switch set point offered at no additional charge. Specify one set point per switch and if load is ascending or descending.
8. Capacity ratings of Dillon's calibration slings may prohibit some switch settings with smaller diameter rope. Call the factory for any limitations.

How to Order:

Example: One unit, 5,000 pounds capacity with pulleys grooved for 5/8" rope diameter, with three weather proof option B switches, set at 2,000, 3,000, and 4000 pounds (all ascending) . Specify by model number: CGS-2-B3, for 5/8" rope diameter. Set switches at 2,000 lb (ascending) 3,000 lb (ascending) and 4,000 lb (ascending).